

# BC 1200 ECO AND BC 1200 ECO WATER

CODE: BC1200ECO - BC1200ECO/WATER

TESTING  
COLLAUDO



WATER VERSION WITH CHAMBER  
AND COMPONENTS IN STAINLESS STEEL  
VERSIONE AD ACQUA CON VASCA  
E COMPONENTI IN ACCIAIO INOX

PROVIDED WITH ONE Ø 1/4" GAS QUICK COUPLING AND  
PNEUMO-HYDRAULIC PUMP  
DOTATO DI UN INNESTO RAPIDO Ø 1/4" GAS E POMPA  
PNEUMO-IDRAULICA

## MAIN FEATURES - CARATTERISTICHE PRINCIPALI



MANUALLY OPERATED  
AZIONAMENTO MANUALE



NOT SUITABLE  
FOR BURST TEST  
NON ADATTO  
A PROVE A SCOPPIO



SHOCK-PROOF  
TESTING WINDOWS  
FINESTRE DI CONTROLLO  
ANTI-URTO



WATER TESTS  
COLLAUDO AD ACQUA

BC 1200ECO/WATER

## TECHNICAL DATA - DATI TECNICI

STATIC PRESSURE PRESSIONE STATICA	1200 BAR (17400 PSI)
MIN. STARTING PRESSURE PRESSIONE MINIMA DI PARTENZA	70 BAR (1015 PSI)
PRESSURE CONTROL CONTROLLO DELLA PRESSIONE	MANUAL
TEST PROCEDURA TEST	MANUAL
TYPE OF DRIVE TIPO DI AZIONAMENTO	PNEUMATIC INTENSIFIER
TESTING LIQUID LIQUIDO DI COLLAUDO	FLUID OR WATER
N° MANIFOLDS N° MASSELLI	1
N° CONNECTIONS PER MANIFOLD N° CONNESSIONI PER MASSELLO	N. 1 SPECIAL QUICK CONNECTION
LIQUID FILLING RIEMPIMENTO LIQUIDO	MANUAL
PRESSURE PUMP FLOW PORTATA POMPA PRESSIONE	0.3 LT./MIN.
PRESSURE DISCHARGE SCARICO PRESSIONE	MANUAL
STANDARD CHAMBER DIMENSIONS DIMENSIONI VASCA STANDARD	1200X550X250 mm
BENCH DIMENSIONS DIMENSIONI BANCO	1500X600X1200 mm
TANK SERBATOIO	30 LT.
WEIGHT WITHOUT OIL (BC 1200 ECO) PESO SENZA OLIO (BC 1200 ECO)	165 KG
WEIGHT WITHOUT WATER (BC 1200 ECO WATER) PESO SENZA ACQUA (BC 1200 ECO WATER)	130 KG
PRESSURE GAUGE MANOMETRO	ANALOGIC

## INCLUDED ACCESSORIES - ACCESSORI INCLUSI

SUCTION FILTER  
FILTRO DI ASPIRAZIONE

DELIVERY FILTER  
FILTRO DI SCARICO

INTERNAL OIL PROTECTING MESH  
RETE ANTIOILIO

ADAPTOR WITH QUICK COUPLING 1/4"  
ADATTATORE MASCHIO CON INNESTO RAPIDO 1/4"

## OPTIONAL - OPZIONALE

ADAPTOR: 3/8" - 1/2" - 3/4" - 1" - 1 1/4" - 1 1/2" - 2"  
ADATTATORE MASCHIO: 3/8" - 1/2" - 3/4" - 1" - 1 1/4" - 1 1/2" - 2"

PRESSURE REPORT KIT  
KIT REPORT PRESSIONE



ADAPTORS  
ADATTATORI



ADAPTOR WITH QUICK COUPLING  
ADATTATORE CON INNESTO RAPIDO